



1660 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **4 strong polyurethane wheels with stainless steel bearings**
- **Large 2-person fold down handles**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1660
Standard



1664
With Padded Dividers



1660NF
No Foam



1660WF
With Foam

DIMENSIONS

Interior (L×W×D)	28.20 x 19.66" x 17.63 (71.6 x 49.9 x 44.8 cm)
Exterior (L×W×D)	31.59 x 22.99" x 19.48 (80.2 x 58.4 x 49.5 cm)
Lid Depth	3.50" (8.9 cm)
Bottom Depth	14.14" (35.9 cm)
Total Depth	17.64" (44.8 cm)
Int Volume	5.66 ft ³ (0.16 m ³)
Padlock Hole Diameter	5/16" (8 mm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS

 Black	 Desert Tan	 OD Green
---	--	--

WEIGHT

Weight With Foam	42.16 lbs (19.1 kg)
Weight Empty	34.16 lbs (15.5 kg)
Buoyancy	365.00 lbs (165.6 kg)
Master Pack Weight	49.00 lbs (22.2 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67
Def Stan 81-41

OTHER

Wheels	4
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Reduced Area	yes
Military	yes

ACCESSORIES

				
1661 5 pc. Replacement Foam Set	1662 Pick N Pluck™ Sections Only (set of 3)	1663 Replacement O-ring	1665 Padded Divider Set	1669 Photo/Lid Organizer
				
1507 Quick Mounts - set of 4	1506TSA TSA Lock	1500D Desiccant Silica Gel	1500CI Corrosion Intercept Kit	

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 03-08-23